



aerospace
 climate control
 electromechanical
filtration
 fluid & gas handling
 hydraulics
 pneumatics
 process control
 sealing & shielding



Marine Retail Basics

Product Overview



ENGINEERING YOUR SUCCESS.

Diesel Fuel Filter/Water Separator

The Racor's fuel filter/water separators feature a variety of compact sizes to fit the most cramped engines. Most units feature 1/4"-18 NPTF inlet and outlet fuel ports and a unitized mounting bracket.

If quality is what you want and filtration is what you need, then a Racor fuel filter/water separators are the answer. Experienced sailors trust their engines, their livelihood and even their lives to Racor. Shouldn't you?



Specifications	110A	120AS
Micron Rating	2	2
Maximum Flow Rate	15 GPH (57 LPH)	15 GPH (57 LPH)
Replacement Filter	R11S	R12S
Height	6.0 in. (15.2 cm)	6.5 in. (16.5 cm)
Weight	1.3 lbs (0.6 kg)	1.1 lbs (0.5 kg)
Width	3.2 in. (8.1 cm)	3.2 in. (8.1 cm)



Specifications	120AP	215R2
Micron Rating	30	2
Maximum Flow Rate	15 GPH (57 LPH)	15 GPH (57 LPH)
Replacement Filter	R12P	R15S
Height	6.5 in. (16.5 cm)	8.3 in. (21.1 cm)
Weight	1.1 lbs (0.5 kg)	1.8 lbs (0.8 kg)
Width	3.2 in. (8.1 cm)	4.0 in. (10.2 cm)



Specifications	230R2	245R2
Micron Rating	2	2
Maximum Flow Rate	30 GPH (114 LPH)	45 GPH (170 LPH)
Replacement Filter	R20S	R25S
Height	9.0 in. (22.9 cm)	10.5 in. (36.7 cm)
Weight	2.0 lbs (0.9 kg)	2.2 lbs (1.0 kg)
Width	3.9 in. (9.9 cm)	3.9 in. (9.9 cm)

Gasoline Filters for Marine Applications

Don't be caught in the water without one of these Racor OEM or gasoline Spin-On series filters. These filters are designed for high performance applications, with flow rates between 30 and 120 GPH your engine

will perform better than ever with clean, water-free fuel. These filters are coated with a durable electrostatically applied powder coating for superior corrosion resistance. That's the quality you've learned to expect from Racor.

ParFit™



Specifications	PFF5510	B32014	B32020MAM
OEM Application	MerCruiser	OMC	MerCruiser
Micron Rating	10	10	10
Maximum Flow Rate	60 GPH (227 LPH)	60 GPH (227 LPH)	60 GPH (227 LPH)
Replacement Filter	N/A	S3214	S3220TUL
Height	4.2 in. (10.7 cm)	7.2 in. (18.3 cm)	6.5 in. (16.7 cm)
Diameter	3.6 in. (9.1 cm)	3.8 in. (9.7 cm)	3.8 in. (9.7 cm)
Center Threads	11/16"-16	1"-12	11/16"-16



Specifications	110A	025-RAC-02	120R-RAC-01	120R-RAC-02
Micron Rating	10	10	10	10
Maximum Flow Rate	35 GPH (132 LPH)	25 GPH (95 LPH)	30 GPH (114 LPH)	30 GPH (114 LPH)
Height	6.0 in. (15.2 cm)	4.3 in. (10.9 cm)	6.5 in. (16.5 cm)	6.5 in. (16.5 cm)
Weight Dry	1.3 lbs (0.6 kg)	0.3 lb (0.1 kg)	1.1 lbs (0.5 kg)	1.1 lbs (0.5 kg)
Width	3.2 in. (8.1 cm)	2.3 in. (5.8 cm)	3.2 in. (8.1 cm)	3.2 in. (8.1 cm)
Center Threads	N/A	N/A	M18 x 1.5	M18 x 1.5
Port Size	1/4"-18 NPTF	1/4"-18 NPT	1/4"-18 NPTF	1/4"-18 NPTF
Replacement Filter	R11T	S2502	S3240	S3240TUL



Specifications	320R-RAC-01	320R-RAC-02	490R-RAC-01	660R-RAC-02
Micron Rating	10	10	10	10
Maximum Flow Rate	60 GPH (227 LPH)	60 GPH (227 LPH)	90 GPH (341 LPH)	90 GPH (341 LPH)
Port Size	1/4"-18 NPTF	1/4"-18 NPTF	3/8"-18 NPTF	3/8"-18 NPTF
Replacement Filter	S3227	S3228TUL	S3227	S3232TUL
Height	9.3 in. (23.6 cm)	9.0 in. (22.8 cm)	9.9 in. (25.1 cm)	10.5 in. (26.7 cm)
Weight Dry	2.0 lbs (0.9 kg)	2.0 lbs (0.9 kg)	2.6 lbs (1.2 kg)	3.0 lbs (1.4 kg)
Width	4.0 in. (10.2 cm)	4.0 in. (10.2 cm)	4.5 in. (11.4 cm)	4.2 in. (10.7 cm)

Replacement Elements



Specifications	S2501	S2502
Micron Rating	250	10
Maximum Flow Rate (with diesel) (with gasoline)	15 GPH (57 LPH) 25 GPH (95 LPH)	15 GPH (57 LPH) 25 GPH (95 LPH)
Description	Element Only	Element Only
Height	N/A	N/A
Thread	N/A	N/A



Specifications	S3204P	S3204TUL	S3209S
Micron Rating	30	10	2
Maximum Flow Rate	40 GPH (151 LPH)	40 GPH (151 LPH)	60 GPH (227 LPH)
Description	Element Only	Element Only	Element Only
Height	4.0 in. (10.2 cm)	4.0 in. (10.2 cm)	5.5 in. (14.0 cm)
Diameter	3.8 in. (9.7 cm)	3.8 in. (9.7 cm)	3.8 in. (9.7 cm)
Thread	1"-14	1"-14	M16 x 1.5



Specifications	S3211TUL	S3213	S3214
Micron Rating	10	10	10
Maximum Flow Rate	90 GPH (341 LPH)	60 GPH (227 LPH)	60 GPH (227 LPH)
Description	Element Only	Element Only	Element Only
Height	5.5 in. (14.0 cm)	4.0 in. (10.2 cm)	4.0 in. (10.2 cm)
Diameter	3.7 in. (9.4 cm)	3.7 in. (9.4 cm)	3.7 in. (9.4 cm)
Thread	1"-14	11/16"-16	1"-12

Replacement Elements



Specifications	S3220SUL	S3220TUL	S3227	S3228TUL
Micron Rating	2	10	10	10
Maximum Flow Rate	60 GPH (227 LPH)	60 GPH (227 LPH)	90 GPH (340 LPH)	60 GPH (227 LPH)
Description	Element Only	Element Only	Element Only	Element Only
Height	4.0 in. (10.2 cm)	4.0 in. (10.2 cm)	4.0 in. (10.2 cm)	4.0 in. (10.2 cm)
Diameter	3.7 in. (9.4 cm)	3.7 in. (9.4 cm)	3.7 in. (9.4 cm)	3.7 in. (9.4 cm)
Thread	11/16"-16	11/16"-16	1"-14	1"-14



Specifications	S3232TUL	S3240TUL	R12P	R12T
Micron Rating	10	10	30	10
Maximum Flow Rate	120 GPH (454 LPH)	30 GPH (114 LPH)	15 GPH (57 LPH)	15 GPH (57 LPH)
Description	Element Only	Element Only	Element Only	Element Only
Height	5.5 in. (14.0 cm)	2.4 in. (6.1 cm)	2.4 in. (6.1 cm)	2.4 in. (6.1 cm)
Diameter	3.7 in. (9.4 cm)	3.0 in. (7.6 cm)	3.0 in. (7.6 cm)	3.0 in. (7.6 cm)
Thread	1"-14	M18 x 1.5	M18 x 1.5	M18 x 1.5



Specifications	R11T	R11S	R15T	R15P
Micron Rating	10	2	10	30
Maximum Flow Rate (with diesel) (with gasoline)	15 GPH (57 LPH) 35 GPH (132 LPH)	15 GPH (57 LPH) 35 GPH (132 LPH)	15 GPH (57 LPH) N/A	15 GPH (57 LPH) N/A
Description	Element Only	Element Only	Element Only	Element Only
Thread	N/A	N/A	1"-14	1"-14

Replacement Elements



Specifications	R15S	R20P	R20T	R24P
Micron Rating	2	30	10	30
Maximum Flow Rate	15 GPH (57 LPH)	15 GPH (57 LPH)	15 GPH (57 LPH)	30 GPH (114 LPH)
Description	Element Only	Element Only	Element Only	Element Only
Height	3.3 in. (8.4 cm)	4.0 in. (10.2 cm)	4.0 in. (10.2 cm)	3.5 in. (8.9 cm)
Diameter	3.7 in. (9.4 cm)	3.7 in. (9.4 cm)	3.7 in. (9.4 cm)	3.6 in. (9.1 cm)
Thread	1"-14	1"-14	1"-14	1"-14



Specifications	R24S	R24SUL	R24T	R25P
Micron Rating	2	2	10	30
Maximum Flow Rate	30 GPH (114 LPH)	30 GPH (114 LPH)	30 GPH (114 LPH)	45 GPH (170 LPH)
Description	Element Only	Element Only	Element Only	Element Only
Height	3.5 in. (8.9 cm)	3.5 in. (8.9 cm)	3.5 in. (8.9 cm)	5.5 in. (14.0 cm)
Diameter	3.6 in. (9.1 cm)	3.6 in. (9.1 cm)	3.6 in. (9.1 cm)	3.7 in. (9.4 cm)
Thread	1"-14	1"-14	1"-14	1"-14



Specifications	R26S	R26SUL	R26T	R45S
Micron Rating	2	2	10	2
Maximum Flow Rate	45 GHP (170 LPH)	45 GHP (170 LPH)	45 GHP (170 LPH)	45 GHP (170 LPH)
Description	Element Only	Element Only	Element Only	Element Only
Height	4.1 in. (10.4 cm)	4.1 in. (10.4 cm)	4.1 in. (10.4 cm)	4.0 in. (10.2 cm)
Diameter	3.7 in. (9.4 cm)	3.7 in. (9.4 cm)	3.7 in. (9.4 cm)	4.3 in. (10.9 cm)
Thread	1"-14	1"-14	1"-14	1"-14

Turbine Series for Marine Applications

Marine Turbine Series filter assemblies are designed to be installed on the vacuum side of the fuel transfer pump for best efficiency and protect precision engine components from dirt, rust, algae, asphaltines, varnishes, and especially water, which is prevalent in engine fuels. They remove contaminants from fuel using the following legendary three stage process:

Stage One: Separation

As fuel enters the filter assembly, it moves through the centrifuge and spins off large solids and water droplets which fall to the bottom of the collection bowl.

Stage Two: Coalescing

Small water droplets bead-up on the surface of the conical baffle and cartridge element. When heavy enough, they too fall to the bottom of the bowl.

Stage Three: Filtration

Proprietary Aquabloc II cartridge elements repel water and remove contaminants from fuel down to 2 micron (nominal). They are waterproof and effective longer than water absorbing elements.



Specifications	75500FGX2	75500MAX2
Maximum Flow Rate: (one unit online) (two unit online)	60 GPH (227 LPH) 120 GPH (454 LPH)	60 GPH (227 LPH) 120 GPH (454 LPH)
Application	Diesel	Diesel
Port Size	3/4"-16 (SAE J1926 female threads)	3/4"-16 (SAE J1926 female threads)
Micron Rating	2	2
Replacement Element	2010 Series	2010 Series
Height	11.5 in. (29.2 cm)	11.5 in. (29.2 cm)
Depth	9.5 in. (24.1 cm)	9.5 in. (24.1 cm)
Width	14.5 in. (36.8 cm)	14.5 in. (36.8 cm)
Weight	17.0 lbs (7.7 kg)	17.0 lbs (7.7 kg)
Clean Pressure Drop	0.7 PSI (4.8 kPa)	0.7 PSI (4.8 kPa)
Maximum Pressure	15 PSI (1 bar)	15 PSI (1 bar)
Water Capacity	3.7 oz (109 ml)	7.4 oz (220 ml)
Overhead Clearance	4.0 in. (10.2 cm)	4.0 in. (10.2 cm)
Water Removal Efficiency	99%	99%
Ambient Fuel Temperature	-40° to +255°F (-40° to +124°C)	-40° to +255°F (-40° to +124°C)
Max Fuel Temperature	190°F (88°C)	190°F (88°C)

Turbine Series for Marine Applications



Specifications	75500MAXM2	791000MAV30
Maximum Flow Rate: (one unit online) (two units online) (three units online)	60 GPH (227 LPH) 120 GPH (454 LPH) N/A	180 GPH (681 LPH) 360 GPH (1363 LPH) 540 GPH (2044 LPH)
Application	Gasoline or Diesel	Gasoline or Diesel
Port Size	3/4"-16 (SAE J1926 female threads)	3/4"-14 (SAE J476 male threads)
Micron Rating	2	30
Replacement Element	2010 Series	2020 Series
Height	11.5 in. (29.2 cm)	22.0 in. (55.9 cm)
Depth	9.5 in. (24.1 cm)	11.8 in. (30.0 cm)
Width	14.5 in. (36.8 cm)	21.5 in. (54.6 cm)
Weight	18.0 lbs (8.2 kg)	52.0 lbs (23.6 kg)
Clean Pressure Drop	0.7 PSI (4.8 kPa)	2.5 PSI (17.2 kPa)
Maximum Pressure	15 PSI (1.0 bar)	15 PSI (1.0 bar)
Water Capacity	7.4 oz (220 ml)	30.9 oz (915 ml)
Overhead Clearance	4.0 in. (10.2 cm)	10.0 in. (25.4 cm)
Water Removal Efficiency	99%	99%
Ambient Fuel Temperature	-40° to +255°F (-40° to +124°C)	-40° to +255°F (-40° to +124°C)
Max Fuel Temperature	190°F (88°C)	190°F (88°C)



Specifications	2010SM-OR 2010TM-OR 2010PM-OR	2020SM-OR 2020TM-OR 2020PM-OR	2040SM-OR 2040TM-OR 2040PM-OR
Micron Rating & Filtration Level	210SM-OR, 2 Micron, Final Filtration 2010TM-OR, 10 Micron, Secondary 2010PM-OR, 30 Micron, Primary ¹	220SM-OR, 2 Micron, Final Filtration 2020TM-OR, 10 Micron, Secondary 2020PM-OR, 30 Micron, Primary ¹	240SM-OR, 2 Micron, Final Filtration 2040TM-OR, 10 Micron, Secondary 2040PM-OR, 30 Micron, Primary ¹
Height	2.7 in. (6.9 cm)	9.6 in. (24.4 cm)	4.6 in. (11.7 cm)
Diameter	3.1 in. (7.9 cm)	4.7 in. (11.9 cm)	4.7 in. (11.9 cm)
Applications	500MA-503MA	1000MA-1003MA	900MA-903MA

Notes: ¹A secondary or final filter is required downstream. Replacement seals included.

Marine Air Filters

Air Filter/Silencer



Specifications	AF M408512	AF M501012	AF M601212	AF M701212**
Max. Air Flow*	800 CFM (378 l/s)	1200 CFM (566 l/s)	1600 CFM (755 l/s)	2000 CFM (944 l/s)
Outlet Diameter	4.0 in. (10.2 cm)	5.0 in. (12.7 cm)	6.0 in. (15.2 cm)	7.0 in. (17.8 cm)
Filter	AF M8040	AF M8050	AF M8060	AF M8070
Length	12.5 in. (31.8 cm)	12.5 in. (31.8 cm)	12.5 in. (31.8 cm)	12.5 in. (31.8 cm)
Depth	9.6 in. (24.4 cm)	11.5 in. (29.2 cm)	13.5 in. (34.3 cm)	13.5 in. (34.3 cm)
Hose Barb Size	1.0 in. (2.5 cm)	1.25 in. (3.2 cm)	1.25 in. (3.2 cm)	1.0 in. (2.5 cm)
Weight	4.2 lbs (1.9 kg)	5.0 lbs (2.3 kg)	8.0 lbs (3.6 kgs)	8.0 lbs (3.6 kgs)
Operating Temperature	-40° to +240°F (-40° to +116°C)			
*Values given are cubic feet per minute (CFM) and liters per second (l/s). **AF M701212-01 is available with a 1.25 in. hose barb.				

CCV Crankcase Filtration



Specifications	CCV1500	CCV4500	CCV6000	CCV8000	CCV12000
Maximum Flow Rate	1 CFM (28 LM)	10 CFM (283 LM)	20 CFM (566 LM)	40 CFM (1133 LM)	50 CFM (1416 LM)
Maximum Engine Rating	40 HP (29.8 KW)	400 HP (298.3 KW)	800 HP (596.6 KW)	1600 HP (1193.1 KW)	2000 HP (1491.4 KW)
Inlet/Outlet Port Size	3/4" hose	1 3/16"-12 STOR	1 5/8"-12 STOR	1 7/8"-12 STOR	1 7/8"-12 STOR
Weight (approx.)	1.5 lbs (0.7 kg)	3.3 lbs (1.5 kg)	5.0 lbs (2.3 kg)	8.7 lbs (3.9 kg)	9.3 lbs (4.2 kg)
Replacement Filter Media Density: Low	CCV55365-04	CCV55248-04	N/A	N/A	N/A
Replacement Filter Media Density: High	N/A	CCV55248-08	CCV55274-08	CCV55222-08	CCV55222-12-08
Replacement Filter Media Density: Ultra	N/A	CCV55248-10	CCV55274-10	CCV55222-10	CCV55222-12-10
Crankcase Pressure Regulator	Vacuum Limiting valve	Integral	Integral	Integral	Integral
Bypass/Change Indicator	N/A	Integral or Remote	Integral or Remote	Integral or Remote	Integral or Remote
Engine Block Check Valve Return Fitting	N/A	1/4" NPT	1/4" NPT	3/8" NPT	3/8" NPT
Swivel Fitting (Qty.)	N/A	#6 JIC (2 pcs.)	#6 JIC (2 pcs.)	#8 JIC (2 pcs.)	#8 JIC (2 pcs.)
Oil Drain Hose I.D.	N/A	0.375 in. (0.95 cm)	0.375 in. (0.95 cm)	0.5 in. (1.27 cm)	0.5 in. (1.27 cm)
Units can be manifolded to handle higher flow rates. Do not use CCV1500 in continuous duty applications.					

Marine Air Filters

Washable Filters
Air Filtration Element



<i>Racor Part Number</i>	Dimensions D x H x D	<i>Racor Part Number</i>	Dimensions D x H x D
<i>AF M8145</i>	10 x 8 x 10	<i>AF M8157</i>	12 x 14 x 12
<i>AF M8121</i>	7.5 x 6 x 7.5	<i>AF M8026</i>	7.5 x 10 x 5.125
<i>AF M8122</i>	7.5 x 7 x 7.5	<i>AF M8025</i>	7.5 x 8 x 5.125
<i>AF M8126</i>	7.5 x 10 x 7.5	<i>AF M8034</i>	9 x 9 x 7
<i>AF M8010</i>	3" Air Separator	<i>AF M8033</i>	9 x 12 x 6.88
<i>AF M8153</i>	12 x 12 x 12	<i>AF M8134</i>	9 x 9 x 9
<i>AF M8037</i>	9 x 14 x 6.875	<i>AF M8133</i>	9 x 12 x 9
<i>AF M8047</i>	10 x 14 x 7	<i>AF M8141</i>	10 x 6 x 10
<i>AF M8152</i>	12 x 7 x 12	<i>AF M8156</i>	12 x 12 x 8

Marine Fuel/Air Separator



Specifications	LG50	LG100
<i>Application:</i>	Gasoline	Gasoline or Diesel
<i>Max. Air Flow Rate</i>	12 CFPM (5.6LPS)	17 CFPM (8.0 LPS)
<i>Hose Barb Size</i>	5/8"	5/8"
<i>Thermal Expansion</i>	2.4 PSI (0.17 bar)	2.4 PSI (0.17 bar)
<i>Height</i>	6.0 in. (15.2 cm)	9.75 in. (24.8 cm)
<i>Diameter</i>	1.8 in. (4.6 cm)	4.0 in. (10.0 cm)
<i>Weight (dry)</i>	1.2 lbs (0.5 kg)	1.6 lbs. (0.7 kg)

Notes: Flow rates are in cubic feet per minute (CFPM) and litter per second (LPS).

Fuel Additives

Racor additives are performance-enhancing products for all climates and seasons. They mix well with fuels and are not removed by fuel filters. The high concentration of active ingredients allows for higher treatment rates. All Racor fuel additives are alcohol-free.



Specifications	Diesel Conditioner Plus+	Diesel Biocide	Gasoline Conditioner Plus+
Part Number	ADT 1201	ADT 2201	ADT 5116
Application	Diesel	Diesel	Multiple Gasoline Blends
Container Size	1 Gallon	1 Gallon	16 Ounces
Treats	2,560 Gallons	10,240 Gallons	320 Gallons

Accessories

Fuel Polishing Module



Specifications	FPM-050
Filtration Rate	50 gallons per day (up to 350 gallons per week)
Power Requirements	Less than 2 watts (less than three hours per day)
Internal Pressure Drop	Less than 0.5 PSI
Voltage Requirements	10-16 VDC, 12 VDC nominal
Approx. Dimensions (Body)	3.8" L x 2.47" H x 2.14" D
(With Bracket)	3.87" L x 4.48" H x 2.14" D
Ports (Inlet & Outlet)	3/8" NPTF Recirculation-1/4" NPFT
Weight	Less than 2 lbs.
Acceptable Fuels	Diesel, Biodiesel or Kerosene
Connections	Includes 18 AWG leads

Notes: Actual flow rate is system dependent.

This application is not compatible and should not be used with gasoline or other flammable liquids.

Bowl Wrench



Specifications	RK-22628
Specifications	Racor offers a hand wrench to remove all metal and see-thru Spin-On bowls that feature external ribs. By simply fitting the wrench over the bowl ribs, the bowl can be removed from the replaceable Spin-On element, or filter housing with little effort. The wrench is made of a corrosion proof, high-impact, high-strength engineered polymer. One bowl wrench per kit.

Diesel Marine Shut-Off Valve



Specifications	RK-19492
Applications (Marine Series) (Marine Turbine Series)	Marine 800 Series Turbine-500MA-503MA Turbine-900MA-903MA Turbine-1000MA-1003MA Turbine-731000MA, 75500MAX, 75900MAX, 751000MAX, 771000MA, 791000MAV
Thread:	
T1	1/4"-18 NPT (male)
T2	1/4"-18 NPT (female) ¹
Material	Brass
Quantity per Kit	1
Notes: ¹ T2 port includes 1/4"-18 NPT plug. Plug must be in valve unless servicing.	

Worldwide Filtration Manufacturing Locations

North America

Compressed Air Treatment

Filtration & Separation/Balston

Haverhill, MA
978 858 0505
www.parker.com/balston

Filtration & Separation/Finite

Oxford, MI
248 628 6400
www.parker.com/finitefilter

Purification, Dehydration & Filtration Division

Lancaster, NY
716 685 4040
www.parker.com/pdf

Sales Office

Charlotte, NC
704 921 9303
www.parker.com/pdf

Engine Filtration & Water Purification

Racor
Modesto, CA
209 521 7860
www.parker.com/racor

Racor

Holly Springs, MS
662 252 2656
www.parker.com/racor

Racor

Beaufort, SC
843 846 3200
www.parker.com/racor

Racor – Village Marine Tec.

Gardena, CA
310 516 9911
desalination.parker.com

Hydraulic Filtration

Hydraulic Filter
Metamora, OH
419 644 4311
www.parker.com/hydraulicfilter

Process Filtration

Process Advanced Filtration
Oxnard, CA
805 604 3400
www.parker.com/processfiltration

Europe

Compressed Air Treatment

domnick hunter Industrial

England NE
+44 (0) 191 402 9000,
www.domnickhunter.com

Hiross Zander

Padova Business Unit
Angelo di Piove Padova, Italy
+39 049 9712 111
www.parker.com/hzde

Hiross Zander

Essen Business Unit
Essen, Germany
T +49 2054 9340, F +49 2054 934164
www.parker.com/hzde

Parker Gas Separations

Etten- Leur, Netherlands
+31 76 508 5300

Engine Filtration & Water Purification

Racor
England
+44 (0) 1924 487000,
www.parker.com/rfde

Racor Research & Development

Stuttgart Germany
+49 (0)711 7071 290-0
www.parker.com/racor

Hydraulic Filtration

Hydraulic Filter
Arnhem, Holland
+31 26 3760376
www.parker.com/eurofilt

Urjala Operation

Urjala as Finland
+358 20 753 2500
www.parker.com/fi

Condition Monitoring Center

Norfolk IP 24 1HP England
+44 1842 763299
www.parker.com/cmc

Process Filtration

domnick hunter Process
DH3 2SF England
T +44 (0) 191 410 5121
www.domnickhunter.com

Asia Pacific

Australia

NSW 2154, Australia
+61 2 9634 777
www.parker.com/australia

China

Shanghai 101206 China
+86 21 5031 2525
www.parker.com/china

India

Mahape, Navi Mumbai 400 709 India
T +91 22 5613 7081, 82, 83, 84, 85
www.parker.com/india

Japan

Yokohama-shi, 244-0003 Japan
T +81 45 870 1522
www.parker.com/japan

Korea

Hwaseong-City Gyeonggi-Do, Korea
T +82 31 359 0771
www.parker.com/korea

Singapore

Singapore 619 702
T +65 6887 6300
www.parker.com/singapore

Thailand

Bangkok 10250 Thailand
T +66 (0)2 186 7024
www.parker.com/thailand

Latin America

Parker Comercio Ltda.

Filtration Division
Sao Jose dos Campos
CEP 12225-390 SP Brazil
+55 12 4009 3500
www.parker.com/br

Pan American Division - Miami

Miami, FL
305 470 8800
www.parker.com/panam

Africa

Aeroporto Kempton Park,
1620 South Africa
+27 11 9610700
www.parker.com/eu



Parker Hannifin Corporation
**Filtration Group Global
Headquarters**

6035 Parkland Boulevard
Cleveland, OH 44124-4141
phone 216 896 3000
fax 216 896 4021
www.parker.com/racor